

Fig. 1a




Fig. 1a
(e.B.)




Fig. 2 (e.B.)




Fig. 3
(sym.)




Fig. 4
(b.b.)




Fig. 5
(e.b.)




Fig. 6
(e.B.)

Profil: SPB - u. 17 - Grauguss

D 1 Wirk Ø	Rillen- zahl	Form	h Kranz- breite mm	d=1 Vor Bohrung ca. mm	ma. mm	N Ø	L Naben- länge mm	Fig.	Gewicht ca. kg
63	1	V	25	ungeb.	25	40	32	1	0,6
71	1	V	25	ungeb.	25	40	35	1	0,7
	2	V	44	ungeb.	30	—	44	1a	1
80	1	V	25	10	35	52	35	1	1
	2	V	44	10	35	—	44	1a	1,3
	3	V	63	12	35	—	63	1a	1,8
90	1	V	25	10	35	56	35	1	1,2
	2	V	44	12	40	—	44	1a	1,6
	3	V	63	12	40	—	50	2	2,2
	4	V	82	12	40	—	82	2	2,9
100	1	V	25	12	35	56	35	1	1,4
	2	V	44	12	40	—	44	1	2,3
	3	V	63	14	40	—	50	2	2,7
	4	V	82	14	45	—	50	2	3,7
112	1	V	25	12	35	56	35	1	1,6
	2	V	44	12	40	56	55	1	2,8
	3	V	63	14	40	—	50	2	3,6
	4	V	82	14	45	—	50	2	3,9
125	1	V	25	12	35	56	35	1	1,7
	2	V	44	12	40	56	55	1	3,1
	3	V	63	14	45	—	50	2	4,6
	4	V	82	14	45	—	50	2	4,7
	5	V	101	14	50	—	50	2	5,3
	6	V	120	14	60	—	60	2	6,3
140	1	V	25	12	35	70	35	5a	2
	2	V	44	12	40	70	55	5a	3,5
	3	V	63	14	45	—	50	2	5,7
	4	V	82	14	45	—	50	2	6
	5	V	101	16	50	—	60	2	7,2
	6	V	120	16	50	—	60	2	8,1
150	1	V	25	12	35	70	40	5a	2,6
	2	V	44	12	40	70	55	5a	4,2
	3	V	63	14	45	—	50	2	5,2
	4	V	82	14	45	—	50	2	6,5
160	1	V	25	12	40	65	40	5	2,6
	2	V	44	12	45	71	55	5	4,2
	3	V	63	14	50	—	50	2	5,4
	4	V	82	14	50	—	60	6	8
	5	V	101	16	50	—	60	2	9
	6	V	120	18	55	—	65	2	9,8
180	1	V	25	12	40	64	40	5	2,8
	2	V	44	12	45	71	50	5	4,5
	3	V	63	14	50	79	50	6	5,9
	4	V	82	16	50	79	60	6	8,4
	5	V	101	18	55	93	70	6	10,8
	6	V	120	18	60	100	70	6	13,6
200	1	V	25	12	40	64	40	5	3,3
	2	V	44	12	45	68	50	5	5,2
	3	V	63	14	50	79	50	6	7,5
	4	V	82	16	50	83	60	6	8,5
	5	V	101	18	55	90	70	6	10,4
	6	V	120	20	60	100	80	6	15,3
224	1	V	25	12	42	70	45	5	4,2
	2	V	44	14	48	78	50	5	6,2
	3	V	63	16	50	83	50	6	7,6
	4	V	82	18	55	105	60	6	9,7
	5	V	101	20	60	100	70	6	12,8
	6	V	120	20	65	110	80	6	17,8
250	1	V	25	12	42	70	45	5	5
	2	V	44	16	48	78	50	5	7,2
	3	V	63	18	55	93	60	6	9,5
	4	V	82	20	60	100	65	6	12,7
	5	V	101	20	65	110	75	6	15,1
	6	V	120	20	65	110	80	6	17,4
280	1	S	25	14	50	80	50	5	6,5
	2	S	44	16	60	95	50	5	8,2
	3	S	63	18	55	95	60	6	11,5
	4	V	82	20	60	100	65	6	14
	5	V	101	20	65	110	75	6	17,3

S = Speichenscheiben V = Bodenscheiben

Profil: SPB - u. 17 - Grauguss




Fig. 1a




Fig. 1a
(e.B.)




Fig. 2 (e.B.)




Fig. 3
(sym.)




Fig. 4
(b.b.)




Fig. 5
(e.b.)




Fig. 6
(e.B.)

D 1 Wirk Ø	Rillen- zahl	Form	h Kranz- breite mm	d=1 Vor Bohrung ca. mm	ma. mm	N Ø	L Naben- länge mm	Fig.	Gewicht ca. kg
315	1	S	25	20	50	80	50	5	6,9
	2	S	44	20	55	90	60	5	10
	3	S	63	20	60	93	60	6	14
	4	S	82	20	60	100	65	6	17,2
	5	S	101	20	65	110	75	6	19,9
	6	S	120	20	75	125	90	6	23,8
355	1	S	25	20	50	80	50	5	7,9
	2	S	44	20	55	90	60	5	11,6
	3	S	63	20	55	93	60	6	15,1
	4	S	82	20	60	100	65	6	17,5
	5	S	101	20	65	110	75	6	22,8
	6	S	120	20	75	125	90	6	28
400	1	S	25	20	55	90	55	5	10
	2	S	44	20	55	90	60	5	14,1
	3	S	63	20	60	100	65	5	18,7
	4	S	82	20	65	110	75	6	22,7
	5	S	101	20	70	120	85	6	28,4
	6	S	120	20	75	125	100	6	32,5
450	2	S	44	20	55	90	60	5	18,5
	3	S	63	20	60	100	65	5	23,5
	4	S	82	20	65	110	75	6	30
	5	S	101	20	70	120	85	6	35,1
	6	S	120	20	75	125	100	6	40,5
500	2	S	44	20	60	100	65	5	20,4
	3	S	63	20	65	110	75	5	27
	4	S	82	20	70	120	85	5	32
	5	S	101	20	75	125	90	6	39,6
	6	S	120	20	80	135	105	6	46
560	3	S	63	20	65	110	75	5	30,5
	4	S	82	20	70	120	85	5	35
	5	S	101	20	75	125	90	6	39,9
	6	S	120	20	80	135	105	6	50,3
630	3	S	63	20	65	110	75	5	34
	4	S	82	20	75	125	90	5	44
	5	S	101	20	80	135	105	5	52,5
	6	S	120	20	90	145	115	5	62,5

S = Speichenscheiben V = Bodenscheiben