

Profil: SPC 22 - Grauguss

B & E
Antriebsselemente GmbH

Lange Straße 6-10
33014 Bad Driburg

www.bue-antriebsselemente.de



Fig. 1a




Fig. 1a
(e.B.)




Fig. 2 (e.B.)




Fig. 3
(sym.)




Fig. 4
(b.b.)




Fig. 5
(e.b.)




Fig. 6
(e.B.)

D 1 Wirk Ø	Rillen- zahl	Form	h Kranz- breite mm	d=1 Vor- Bohrung ca. mm	ma. mm	N Ø	L Naben- länge mm	Fig.	Gewicht ca. kg
160	1	V	34	12	45	75	50	5	3,5
180	1	V	34	12	45	75	50	5	4
200	1	V	34	12	45	75	50	5	7
	2	V	59,5	12	45	75	50	6	8,5
	3	V	85	16	55	90	70	6	11,5
	4	V	110	16	60	100	70	6	14
	5	V	136	20	65	--	80	2	17
	6	V	161,5	20	70	--	90	2	21
	7	V	187	20	75	--	100	2	23
	8	V	212,5	20	75	--	100	2	30
	9	V	238	20	80	--	110	2	33,5
	10	V	263,5	20	80	--	120	2	38
224	1	V	34	12	45	75	50	5	7,5
	2	V	59,5	12	45	75	50	6	10,5
	3	V	85	16	60	100	70	6	15
	4	V	110,5	16	65	110	80	6	18
	5	V	136	20	70	--	90	2	23
	6	V	161,5	20	75	--	100	2	27
	7	V	187	20	80	--	100	2	31
	8	V	212,5	20	85	--	110	2	35
	9	V	238	20	85	--	120	2	40
	10	V	263,5	20	90	--	140	2	45
250	1	V	34	14	50	80	70	5	9,5
	2	V	59,5	14	50	80	70	5	14
	3	V	85	18	65	110	80	6	17
	4	V	110	18	70	120	90	6	21
	5	V	136	20	75	125	100	6	25
	6	V	161,5	20	80	135	100	6	29
	7	V	187	20	80	--	100	2	39
	8	V	212,5	20	85	--	110	2	44
	9	V	238	20	90	--	120	2	49
	10	V	263,5	20	90	--	140	2	53
280	1	V	34	14	50	80	70	5	12
	2	V	59,5	14	50	80	70	5	16
	3	V	85	20	70	120	90	5	20
	4	V	110	20	75	125	100	6	24
	5	V	136	20	75	125	100	6	29
	6	V	161,5	20	80	135	100	6	34
	7	V	187	20	85	--	110	2	41
	8	V	212,5	20	90	--	120	2	48
	9	V	238	20	90	--	120	2	51
	10	V	263,5	20	95	--	140	2	58
315	1	V	34	14	50	80	70	5	15
	2	V	59,5	14	50	80	70	5	17
	3	V	85	20	70	120	90	5	24
	4	V	110	20	75	125	100	6	28
	5	V	136	20	80	135	100	6	34
	6	V	161,5	20	85	140	110	6	40
	7	V	187	20	90	145	120	6	48
	8	V	212,5	20	95	--	120	2	54
	9	V	238	20	95	--	120	2	60
	10	V	263,5	20	100	--	140	2	66
355	2	V	34	16	55	90	80	5	20
	3	V	59,5	20	70	120	100	5	28
	4	V	85	20	80	135	100	6	33
	5	V	110,5	20	85	140	110	6	40
	6	V	136	20	90	145	120	6	47
	7	V	161,5	20	95	150	120	6	54
	8	V	212,5	20	100	155	140	6	62
	9	V	238	20	100	155	140	6	68
	10	V	263,5	20	105	190	140	6	74
400	3	S	85	20	75	125	100	5	33
	4	V	110,5	20	85	140	110	6	40
	5	V	136	20	90	145	120	6	48
	6	V	161,5	20	95	150	120	6	52
	7	V	187	20	95	150	120	6	62
	8	V	212,5	20	100	155	140	6	70
	9	V	238	20	105	190	120	6	78
	10	V	263,5	20	110	190	140	6	88

S = Speichenscheiben V = Bodenscheiben

Profil: SPC 22 - Grauguss




Fig. 1a




Fig. 1a
(e.B.)




Fig. 2 (e.B.)




Fig. 3
(sym.)




Fig. 4
(b.b.)




Fig. 5
(e.b.)




Fig. 6
(e.B.)

D 1 Wirk Ø	Rillen- zahl	Form	h Kranz- breite mm	d=1 Vor Bohrung ca. mm	ma. mm	N Ø	L Naben- länge mm	Fig.	Gewicht ca. kg
450	3	S	85	20	80	135	100	5	38
	4	S	110,5	20	85	140	110	6	46
	5	V	136	20	95	150	120	6	52
	6	V	161,5	20	100	155	140	6	62
	7	V	187	20	100	155	140	6	73
	8	V	212,5	20	105	190	140	6	81
	9	V	238	20	110	190	160	6	92
	10	V	263,5	20	110	190	160	6	101
500	3	S	85	20	85	140	110	5	42
	4	S	110,5	20	90	145	120	5	50
	5	S	136	20	100	155	140	5	60
	6	S	161,5	20	100	155	140	6	71
	7	V	187	20	105	190	140	6	83
	8	V	212,5	20	110	190	160	6	95
	9	V	238	20	115	200	160	6	105
	10	V	263,5	20	115	200	160	6	116
560	3	S	85	20	85	140	110	5	47
	4	S	110,5	20	90	150	120	5	55
	5	S	136	20	100	155	140	5	66
	6	S	161,5	20	105	190	140	6	77
	7	V	187	20	110	190	160	6	86
	8	V	212,5	20	115	200	160	6	94
	9	V	238	20	115	200	160	6	105
	10	V	263,5	20	120	205	180	6	115
630	3	S	85	20	90	145	120	5	52
	4	S	110,5	20	100	155	140	5	66
	5	S	136	20	105	190	140	5	76
	6	S	161,5	20	110	190	160	6	91
	7	S	187	20	115	200	160	6	107
	8	S	212,5	20	120	205	180	6	126
	9	S	238	20	120	205	180	6	136
	10	S	263,5	20	125	220	180	6	150
710	3	S	85	20	95	150	120	5	64
	4	S	110,5	20	100	155	140	5	79
	5	S	136	20	105	190	140	5	93
	6	S	161,5	20	110	190	160	6	109
	7	V	187	20	120	205	180	6	126
	8	V	212,5	20	120	205	180	6	138
	9	V	238	20	125	220	180	6	153
	10	V	263,5	20	130	220	200	6	173
800	3	S	85	20	95	150	120	5	75
	4	S	110,5	20	105	190	140	5	92
	5	S	136	20	110	190	160	5	114
	6	S	161,5	20	115	200	160	6	130
	7	V	187	20	120	205	180	6	149
	8	V	212,5	20	125	220	180	6	160
	9	V	238	20	130	220	200	6	181
	10	V	263,5	20	135	230	220	6	197
900	3	S	85	20	100	155	140	5	88
	4	S	110,5	20	110	190	160	5	112
	5	S	136	20	115	200	160	5	130
	6	S	161,5	20	120	205	180	5	150
	7	S	187	20	125	220	180	6	176
	8	S	212,5	20	130	220	200	6	196
	9	S	238	20	135	230	220	6	211
	10	S	263,5	20	140	240	220	6	231
1000	3	S	85	20	100	155	140	5	103
	4	S	110,5	20	110	190	160	5	125
	5	S	136	20	120	205	180	5	152
	6	S	161,5	20	125	220	180	5	173
	7	S	187	20	130	220	200	5	203
	8	S	212,5	20	135	230	220	5	221
	9	S	238	20	140	240	220	6	244
	10	S	263,5	20	145	240	240	6	269

S = Speichenscheiben V = Bodenscheiben

Profil: SPC 22 - Grauguss




Fig. 1a




Fig. 1a
(e.B.)




Fig. 2 (e.B.)




Fig. 3
(sym.)




Fig. 4
(b.b.)




Fig. 5
(e.b.)




Fig. 6
(e.B.)

D 1 Wirk Ø	Rillen- zahl	Form	h Kranz- breite mm	d=1 Vor Bohrung ca. mm	ma. mm	N Ø	L Naben- länge mm	Fig.	Gewicht ca. kg
1120	3	S	85	30	100	155	150	5	128
	4	S	110,5	30	115	200	160	5	150
	5	S	136	30	120	205	180	5	171
	6	S	161,5	30	130	220	200	5	201
	7	S	187	30	135	230	220	5	238
	8	S	212,5	30	140	240	220	5	263
	9	S	238	30	145	240	240	5	290
	10	S	263,5	30	150	250	240	6	310
	3	S	85	30	100	155	150	5	140
	4	S	110,5	30	120	205	180	5	173
1250	5	S	136	30	125	220	180	5	203
	6	S	161,5	30	130	220	200	5	237
	7	S	187	30	140	240	220	5	266
	8	S	212,5	30	145	240	240	5	306
	9	S	238	30	150	250	240	5	331
	10	S	263,5	30	155	260	240	6	374

S = Speichenscheiben V = Bodenscheiben