

Profil: 25 - Grauguss




Fig. 1a




Fig. 1a
(e.B.)




Fig. 2 (e.B.)




Fig. 3
(sym.)




Fig. 4
(b.b.)




Fig. 5
(e.b.)











Fig. 6
(e.B.)

D 1 Wirk Ø	Rillen- zahl	Form	h Kranz- breite mm	d=1 Vor- Bohrung ca. mm	ma. mm	N Ø	L Naben- länge mm	Fig.	Gewicht ca. kg
*sym.									
160	1	V	35	12	45	75	50	5	4,5
180	1	V	35	12	45	75	50	5	5,5
200	1	V	35	12	45	75	60	5	7
	2	V	65	12	45	75	60	5	10
	3	V	96	16	55	90	70	6	13
	4	V	125	16	60	100	80	6	15
	5	V	154	20	65	110	90	6	19
	6	V	183	20	70	--	100	2	22
	7	V	212	20	75	--	110	2	25
	8	V	241	20	80	--	120	2	31
	9	V	270	20	80	--	140	2	36
	10	V	299	20	85	--	140	2	40
224	1	V	35	12	45	75	60	5	9
	2	V	65	12	45	75	70	5	12
	3	V	96	16	60	100	70	6	15
	4	V	125	16	65	110	80	6	18
	5	V	154	20	70	120	90	6	22
	6	V	183	20	75	--	100	2	26
	7	V	212	20	80	--	110	2	29
	8	V	241	20	85	--	120	2	37
	9	V	270	20	85	--	140	2	42
	10	V	299	20	90	--	140	2	46
250	1	V	35	14	50	80	70	3	11
	2	V	65	14	50	80	70	5	14
	3	V	96	18	65	110	80	6	17
	4	V	125	18	70	120	90	6	22
	5	V	154	20	75	125	100	6	26
	6	V	183	20	80	135	100	6	32
	7	V	212	20	80	--	110	2	36
	8	V	241	20	85	--	120	2	43
	9	V	270	20	90	--	140	2	50
	10	V	299	20	90	--	140	2	57
280	1*	S	35	14	50	80	70	3	13
	2	S	65	14	50	80	80	5	17
	3	S	96	20	70	120	90	6	21
	4	V	125	20	75	125	100	6	26
	5	V	154	20	75	125	100	6	31
	6	V	183	20	80	135	100	6	36
	7	V	212	20	85	--	110	2	41
	8	V	241	20	90	--	120	2	48
	9	V	270	20	90	--	140	2	57
	10	V	299	20	95	--	140	2	62
315	1*	S	35	14	50	80	70	3	16
	2	S	65	14	50	80	80	5	20
	3	S	96	20	70	120	90	6	23
	4	S	125	20	75	125	100	6	28
	5	S	154	20	80	135	100	6	34
	6	S	183	20	85	140	110	6	40
	7	V	212	20	90	145	120	6	46
	8	V	241	20	95	--	120	2	53
	9	V	270	20	95	--	140	2	61
	10	V	299	20	100	--	140	2	67
355	2	S	65	16	50	80	90	5	22
	3	S	96	20	70	120	100	5	27
	4	S	125	20	70	120	100	6	33
	5	S	154	20	70	120	110	6	39
	6	S	183	20	70	120	120	6	46
	7	V	212	20	95	150	120	6	54
	8	V	241	20	100	155	140	6	62
	9	V	270	20	100	155	140	6	69
	10	V	299	20	105	190	140	6	77
400	3	S	96	20	70	120	100	5	31
	4	S	125	20	70	120	110	6	38
	5	S	154	20	70	120	120	6	45
	6	S	183	20	70	120	120	6	54
	7	V	212	20	95	150	120	6	60
	8	V	241	20	100	155	140	6	69
	9	V	270	20	105	190	140	6	77
	10	V	299	20	110	190	160	6	88

S = Speichenscheiben V = Bodenscheiben



Profil: 25 - Grauguss



D 1 Wirk Ø	Rillen- zahl	Form	h Kranz- breite mm	d=1 Vor Bohrung ca. mm	ma. mm	N Ø	L Naben- länge mm	Fig.	Gewicht ca. kg
*sym.									
450	3	S	96	20	70	120	100	5	31
	4	S	125	20	70	120	110	6	38
	5	S	154	20	70	120	120	6	45
	6	S	183	20	70	120	120	6	54
	7	V	212	20	95	150	120	6	60
	8	V	241	20	100	155	140	6	69
	9	V	270	20	105	190	140	6	77
	10	V	299	20	110	190	160	6	88
500	3	S	96	20	70	120	100	5	31
	4	S	125	20	70	120	110	6	38
	5	S	154	20	70	120	120	6	45
	6	S	183	20	70	120	120	6	54
	7	V	212	20	95	150	120	6	60
	8	V	241	20	100	155	140	6	69
	9	V	270	20	105	190	140	6	77
	10	V	299	20	110	190	160	6	88
560	3	S	96	20	70	120	120	5	46
	4	S	125	20	75	125	120	6	58
	5	S	154	20	75	125	140	6	72
	6	S	183	20	75	125	140	6	83
	7	V	212	20	110	190	160	6	90
	8	V	241	20	115	200	160	6	103
	9	V	270	20	115	200	160	6	111
	10	V	299	20	120	205	180	6	122
630	3	S	96	20	70	120	120	5	53
	4	S	125	20	75	125	140	6	69
	5	S	154	20	75	125	140	6	83
	6	S	183	20	75	125	160	6	97
	7	S	212	20	110	190	160	6	105
	8	S	241	20	115	200	180	6	116
	9	S	270	20	115	200	180	6	126
	10	S	299	20	120	205	180	6	142
710	3	S	96	20	90	145	120	5	61
	4	S	125	20	95	150	140	5	74
	5	S	154	20	100	155	140	6	87
	6	S	183	20	105	190	160	6	105
	7	S	212	20	115	200	180	6	118
	8	S	241	20	115	200	180	6	129
	9	S	270	20	120	205	180	6	146
	10	S	299	20	125	220	200	6	164
800	3	S	96	20	90	145	120	5	69
	4	S	125	20	100	155	140	5	85
	5	S	154	20	105	190	160	5	103
	6	S	183	20	110	190	160	6	121
	7	S	212	20	115	200	180	6	139
	8	S	241	20	120	205	180	6	154
	9	S	270	20	125	220	200	6	172
	10	S	299	20	130	220	200	6	186
900	3	S	96	20	95	150	140	5	87
	4	S	125	20	105	190	160	5	108
	5	S	154	20	110	190	160	5	124
	6	S	183	20	115	200	180	6	148
	7	S	212	20	120	205	180	6	170
	8	S	241	20	125	220	200	6	188
	9	S	270	20	130	220	220	6	210
	10	S	299	20	135	230	220	6	226
1000	3	S	96	20	95	150	140	5	97
	4	S	125	20	105	190	160	5	124
	5	S	154	20	115	200	180	5	148
	6	S	183	20	120	205	180	6	174
	7	S	212	20	125	220	200	6	196
	8	S	241	20	130	220	220	6	215
	9	S	270	20	135	230	220	6	236
	10	S	299	20	140	240	240	6	260

S = Speichenscheiben V = Bodenscheiben

Profil: 25 - Grauguss




Fig. 1a




Fig. 1a
(e.B.)




Fig. 2 (e.B.)




Fig. 3
(sym.)




Fig. 4
(b.b.)




Fig. 5
(e.b.)




Fig. 6
(e.B.)

D 1 Wirk Ø	Rillen- zahl	Form	h Kranz- breite mm	d=1 Vor Bohrung ca. mm	ma. mm	N Ø	L Naben- länge mm	Fig.	Gewicht ca. kg
									*sym.
1120	3	S	96	30	95	150	150	5	97
	4	S	125	30	110	190	160	5	124
	5	S	154	30	115	200	180	5	148
	6	S	183	30	125	220	200	5	174
	7	S	212	30	130	220	220	5	196
	8	S	241	30	135	230	220	6	215
	9	S	270	30	140	240	240	6	236
	10	S	299	30	145	240	240	6	260
1250	3	S	96	30	85	140	150	5	97
	4	S	125	30	115	200	180	5	124
	5	S	154	30	120	205	180	5	148
	6	S	183	30	125	220	200	5	174
	7	S	212	30	135	230	220	5	196
	8	S	241	30	140	240	240	6	215
	9	S	270	30	145	240	240	6	236
	10	S	299	30	150	250	240	6	260

S = Speichenscheiben V = Bodenscheiben